



**BROTHERS**<sup>®</sup>  
PHARMAMACH (INDIA) PVT. LTD.

# LABELSTIK 120H

## Automatic Horizontal Sticker Labelling Machine

The Automatic Horizontal Sticker Labelling Machine Model LABELSTIK-120H, is one of the most user friendly. The Machine incorporates latest sophisticated Micro Processor Control Label Dispensing system with user friendly Sensing system for Label and Product. The machine is suitable for Labelling on unstable small diameter round objects. It is capable of Labelling up to 100 units per minute depending on product diameter and label size. Machine suitable for Round Pre Filled Syringes, Ampoules, Vials, Inhalers, Roll On, Test Tubes and other Small Sizes of round objects. Machine with Optional Product feeding hopper for regular shaped round objects for continues feeding. Feeding of product on machine conveyor is manually by operator for non standard product such as PFS, Blood Collection Tube with Cap hence in such case speed of machine is depending on product feeding speed of operator. Machine can be supplied with Automatic Feeder system having hopper and star wheel for Straight body cylindrical products only as optional items.

The Sticker Labelling Machine LABELSTIK-120H has its own unique single point synchronised speed control system. The Inbuilt Automated Label Length detection systems eliminates any need for manually feeding and storing of Label Length data in memory and retrieving the same every time for change of Label Size & re-starting the machine. The System thus saves valuable time, avoiding machine-down time, and helps achieve higher production. Machine can be supplied with Optional Toughened (Tampered) Glass or Acrylic Safety Cabinet. Machines having required all basic features as a standard fitment to match the current market needs and also saves cost and time.



### TECHNICAL SPECIFICATIONS

- Label Height : 8 mm to 70 mm Standard\*
- Label Length : 12 mm Minimum
- Label Roll Dia. : 400 mm
- Core Dia. : 75/76 mm
- Gap Between two Labels : appx. 3 mm
- Product Diameter : Machine having customized Product holding bracket with roller system hence required actual samples.
- Electrical : 220 VAC Single Phase Power Supply (50/60 Hz)
- Power : 1.0 Hp, 1.5 Amp.
- Capacity : 0.75 Kw
- Speed : Up to 100 Labels per minute depending on Product and Label Size
- Conveyor height : 830-875 mm\*
- Overall dimension : 2440 mm(L) X 760 mm(W) X 1700 mm (H)
- Machine Direction of Movement : Left to Right from operator side

\* Specification can be changed as per customers requirements

**For Built-in / Optional\* Items Refer UNIQUE FEATURES Page for more details.**

### Other Available Models

|                     |                     |                 |                |
|---------------------|---------------------|-----------------|----------------|
| LABELSTIK-120C.Twin | LABELSTIK-120C      | LABELSTIK-150   | LABELSTIK-150B |
| LABELSTIK-250C.Twin | LABELSTIK-300HG     | LABELSTIK-300LR | LABELSTIK-300  |
| LABELSTIK-120R.Twin | LABELSTIK-120R      | LABELSTIK-600   | LABELSTIK-400  |
| LABELSTIK-100F.Twin | LABELSTIK-250F.Twin | LABELSTIK-EXCEL | LABELTUBE-60   |

Email : sales@brothers.in  
Export : sales1@brothers.in

Phone : +91 79 40213213 / 25831346

www.brothersindia.com