

Automatic High Speed Shrink Label Inserting with Shrink Tunnel

Sleev PACK

Automatic Hi

300

Working ideas

Into reality

Working ideas

Into reality

Working ideas

Working

The Automatic High Speed Shrink Label Inserting Machine Model SleevPACK-300 with Option of Shrink Tunnel is suitable to Insert Shrink Label on Glass, Plastic, PET, Aluminium Bottles and Containers in FOOD, FMCG, Pesticides, Cosmetics and Pharmaceutical Industries. The Machine incorporates latest sophisticated SERVO Control Sleeve Applicator. The Machine Construction in Heavy Duty S.S.304 Material but with Compact design

This Flexible Sleeving Machine is suitable for decoration of wide range of Round Bottles and Containers. Special machine also available for special shape containers. Machine can give speed upto 300 Bottles per minute depending on Sleeve Cut Length, Shape of Bottle and Shrink percentage of Sleeve. Machine with Optional Pre-Fixing Hot Air Nozzle for Setting Sleeve Position at Top or Bottlom of Bottles before entering into Shrink Tunnel.

Sleeving Machine having Time Tested Rotating type SERVO Controlled Sleeve Cutting System for high Speed and accurate sleeve cutting. Machine is ideal to use on Round and other curve shape Bottle or Containers where Sticker Labelling is not possible to use.

OPTIONAL FEATURES:

- Tower Light showing the machine status / operation
- Vision System for checking Presence / Absence of Sleeve on Bottle
- Infeed Jam detection system
- Outfeed Jam detection system

TECHNICAL SPECIFICATIONS

Sleeve Height: 50 mm to 150 mm Standard*

Bottle Height: up to 225 mm Sleeve Roll Dia.: 400 mm Core Dia.: 75/76 mm

Sleeve Thickness: 0.045mm to 0.08mm

Product Diameter: User can choose any one option

25 to 50mm / 45 to 90mm or 90 to 125mm*

Electrical: 415 VAC 3 Phase Power Supply (50/60 Hz) Power: 2.5 Kw for Machine and 20 Kw for Shrink Tunnel

Speed: Up to 300 Products per minute depending on Product Diameter,

Product Height and Sleeve Cutting Length.

Conveyor height: 900 to 950 mm*

Overall dimension: 2440 mm(L) X 1000 mm(W) X 1900 mm (H) Machine with Shrink Tunnel: 4880 mm(L) X 1000 mm(W) X 1900 mm (H) Machine Direction of Movement: Left to Right from operator side

* Specification can be changed as per customers requirements

BUILT-IN UNIQUE FEATURES:

- Colour Touch Screen Operation Panel with PLC Control
- Virtually Maintenance Free Machine
- Synchronized speed of Sleeve Dispensing, Conveyor and Sleeve Positioning Device.

BROTHERS PHARMAMACH (INDIA) PVF LTD

- Easy to change Sleeve application height

Phone: +91 79 40213213 / 25831346

- Heavy Duty S.S. 304 Material Machine Frame Structure
- S.S.304 Material heavy duty Safety Cabinet with Toughened Glass
- Built In A.C. Variable Frequency Drive System.

Email: sales@brothers.in Export: sales1@brothers.in

www.brothersindia.com